

Enchufe recto macho cónico - RPD MR




Características técnicas

Presión de uso : 0 a 10 bar

Temperatura : 0°C a + 60°C

Material : Polímero y latón
niquelado

Material: latón niquelado



A (mm)	B (mm)	C (mm)	D (mm)	Rosca macho BSPT	Para tubo Ø ext. (mm)	Referencia
21	11.5	10	13.5	R 1/8	4	RPD MR0400
20	16	14	11	R 1/4	4	RPD MR0401
22	14	12	14.5	R 1/8	5	RPD MR0500
21	16	14	12	R 1/4	5	RPD MR0501
23	19.5	17	12	R 3/8	5	RPD MR0502
25.5	24	21	12.5	R 1/2	5	RPD MR0503
22	14	12	14.5	R 1/8	6	RPD MR0600
21	16	14	12	R 1/4	6	RPD MR0601
23	19.5	17	12	R 3/8	6	RPD MR0602
25.5	24	21	12.5	R 1/2	6	RPD MR0603
27	16	14	19.5	R 1/8	8	RPD MR0800
24	16	14	15	R 1/4	8	RPD MR0801
24.5	19.5	17	13.5	R 3/8	8	RPD MR0802
26	24	21	13	R 1/2	8	RPD MR0803
28	19.5	17	20.5	R 1/8	10	RPD MR1000
29	19.5	17	20	R 1/4	10	RPD MR1001
27	19.5	17	16	R 3/8	10	RPD MR1002
26	24	21	13	R 1/2	10	RPD MR1003
33	22	19	24	R 1/4	12	RPD MR1201
29.5	22	19	18.5	R 3/8	12	RPD MR1202
27.5	24	21	8	R 1/2	12	RPD MR1203
33.1	25	22	22.1	R 3/8	14	RPD MR1402

A (mm)	B (mm)	C (mm)	D (mm)	Rosca macho BSPT	Para tubo Ø ext. (mm)	Referencia
31.2	25	22	18.2	R 1/2	14	RPD MR1403
35	27.5	24	24	R 3/8	16	RPD MR1602
33	27.5	24	20	R 1/2	16	RPD MR1603